


FOUR ROLLER DOSING APPLICATOR

Type: CN 81



- Powered adhesive applicator rollers Ø170 – 0.75 kW
- Dosing rollers are made of stainless steel. They are friction-driven with contact to the applicator rollers, preventing build-up of adhesive that may harden or exceed pot life before application to work piece.
- Dosing rollers are prepared for installation of rotary couplings for connection to cooling equipment.
- Adjustment of thickness of work piece is done quickly and accurately using hand wheel with numeric indicator.
- Dosing rollers are adjusted using handles with impact stop.
- Equipped with 3 support rollers.

Type/ Roller length	Max. application width	Pass-through speed	Workpiece thickness	Equipment dimensions height x length x width - weight
CN 81 – 750 mm	734 mm	Approx. 25 m/min.	2–100 mm	1250 x 1550 x 500 mm – 425 kg
CN 81 – 1000 mm	984 mm	-	-	1250 x 1750 x 500 mm – 525 kg
CN 81 – 1350 mm	1334 mm	-	-	1250 x 2100 x 500 mm – 650 kg

KUNI

MASKINFABRIK A/S

HOLMBLADSVEJ 2
DK-8600 SILKEBORG

E-mail: kuni@kuni.dk



+45 8682 3944



+45 8682 3625

Internet: www.kuni.dk