


FOUR ROLLER DOSING APPLICATOR

Type: LMD-F HD



- Direct drive on all four rollers with gear motors. This improves the possibility for regulating the application of adhesive, and consequently ensures a better quality.
- Has quick-change of applicator rollers, increasing the efficient production time considerably.
- Built-in spring relief between rollers to secure against overload of the rollers.
- The dosing rollers are prepared for mounting of rotary couplings for connection to cooling equipment.
- Adjustment of the machine is done quickly and accurately using hand wheel with numeric indicator scale ensuring identical settings every time.
- Stainless steel has been used for components that have contact with the adhesive, e.g. dosing rollers, flanges, shaft ends, in-/outlet rollers and drip tray.
- Equipped with powered inlet and outlet rollers that may be dismantled.
- Motorised adjustment of height. The height is indicated in the display.

Type/ Roller length	Adh. rollers/ Output	Dos. rollers/ Output	Pass-through speed	Workpiece thickness	Equipment dimensions height x length x width - weight
LMD-F HD 2000 mm	Ø306 mm/ 2 x 1.5 kW	Ø216 mm 2 x 1.1 kW	27 m/min.	2-100 mm	1920 x 3170 x 1110 mm- 1700 kg
LMD-F HD 2300 mm	-	-	-	-	1920 x 3470 x 1110 mm- 1900 kg
LMD-F HD 2700 mm	-	-	-	-	1920 x 3870 x 1110 mm- 2200 kg



MASKINFABRIK A/S

**HOLMBLADSVEJ 2
DK-8600 SILKEBORG**

E-mail: kuni@kuni.dk



+45 8682 3944

+45 8682 3625

Internet: www.kuni.dk